Cam Lock Ø19 mm (%")



Applications

Mul-T-Lock cam locks are available in various sizes, making them suitable for a wide range of applications: cabinets, drawers, parking meters, lockers, cash boxes, payphones etc.

Operation

Retaining: 90°,180° cam rotation Non-retaining: 90° cam rotation Adjustable for clockwise or counter-clockwise operation.

Materials

Body, plug and ring: brass

Cam: steel

Pins: nickel silver and stainless

steel

Standard finishes

Nickel satin, brass

Cylinder mechanism

Mul-T-Lock's unique, high precision pin tumbler system.

Keys

Reversible nickel silver key with plastic key head and colored insert for identification. Also available in all nickel silver.


Cylinder options

- Classic, Interactive®+ platforms
- · Keyed different, keyed alike
- Master keyed
- · Variety of cams

Standard

UL 437

Retaining key




Retaining key hardware set:

- 1 flat cam
- 1 offset cam
- 1 spacer ring 3.4 mm
- 1 spacer ring 9.4 mm
- 1 plate for wood application

A	6
	(0.236")
	19 (Ø3/4")


	Α	Spacer	Chambers
Inch	5/8"	9.5	4
mm	15.9		4
Inch	7/8"	N/A	4
mm	22.2		4
Inch	7/8"	Included	5
mm	22.2	in set	5
Inch	11⁄8"	Included	5
mm	28.6	in set	5
Inch	1½"	Included in set	5
mm	38.1		5


Non-retaining key



Non-retaining hardware set:

- 1 flat cam
- 1 spacer ring 3.4 mm
- 1 spacer ring 8.0 mm
- 1 plate for wood application





Opening required for installation

